



Mobile column

EHB905V20DC wireless

article no.: EHB905V20DC01-H

Our mobile column EHB905V20DC wireless is adapted for tractors and other agricultural vehicles. It is characterised by its capacity of 5 tons and the maximum wheel diameter of 2000 mm. The wheel forks have a length of 600 mm.

• set of 4 mobile columns: 4 x EHB905V20DC01-H



specifications

article no.		EHB905V20DC01-H
lifting unit	type of columns	all columns identical
inung unit	, ,	10
lood ournest	quantity of columns, maximum	
load support	load support	adjustable wheel fork 5 t
	capacity per column	550 mm
	wheel size Ø minimum (mm)	
	wheel size Ø maximum (mm)	2000 mm
1160	length of fork (mm)	600 mm
lifting height	lifting stroke effective	1750 mm
	lifting height	1850 mm
	frame height at front (mm)	155 mm
speed	lifting time	90 sec.
	lowering time (under load)	90 sec.
drive	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
power supply	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	30
	fuse, per column (Amps)	2.5 A
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
	charging time	8 h
communication		communication via radio, wireless
operation	mode of operation	operation at each column
	activation	all, individual, pair
	control	electronic
	Softstart	X
regularisation	synchronisation	proportional valves, infinitely variable
travelling device	travelling device	at each column
	travelling device at front	2 front wheels, fixed
	travelling device at rear	1 hydraulic pallet jack with twin wheels
	ground clearance at front	15 mm
	ground clearance at rear	90 mm
load securing	load securing	hydraulic and mechanical
dimensions	length	1460 mm
	width	1565 mm
	height	2255 mm
	height of fork (mm)	100 mm





weight	weight per column (kgs)	632 kg
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015



Walter Finkbeiner GmbH Tel. +49 (0)7441-92521-0
Alte Poststrasse 9/11 info@finkbeiner.eu

72250 Freudenstadt

Germany

info@finkbeiner.eu www.finkbeiner-lifts.com



accessories



HS08LR support stand, 8.2 t, 1260-1990



Walter Finkbeiner GmbH Tel. +49 (0)7441-92521-0 Alte Poststrasse 9/11

72250 Freudenstadt

Germany

info@finkbeiner.eu www.finkbeiner-lifts.com