



## Mobile column

### **EHB907V25DC wireless**

article no.: EHB907V25DC01-H

The mobile column EHB907V25DC with a capacity of 7.5 tons is perfectly adapted for tractors and agricultural vehicles having a wheel diameter of up to 2500 mm. Due to the fork length of 700 mm, safe lifting is guaranteed. Example for lift sets consisting of identical columns:

- set of 4 columns: 4 x EHB907V25DC01-H



## specifications

<b>article no.</b>		EHB907V25DC01-H
<b>lifting unit</b>	type of columns	all columns identical
	quantity of columns, maximum	10
<b>load support</b>	load support	adjustable wheel fork
	capacity per column	7.5 t
	wheel size Ø minimum (mm)	500 mm
	wheel size Ø maximum (mm)	2500 mm
<b>lifting height</b>	length of fork (mm)	700 mm
	lifting stroke effective	1750 mm
	lifting height	1850 mm
<b>speed</b>	frame height at front (mm)	170 mm
	lifting time	90 sec.
	lowering time (under load)	90 sec.
<b>drive</b>	mode of drive	electro-hydraulic
	motor	DC voltage
	motor power per column (kW)	2.2 KW
<b>power supply</b>	type of power supply	battery-powered
	type of battery	deep cycle, maintenance-free
	battery capacity per column	80 Ah
	lift cycles at full load	15
	fuse, per column (Amps)	2.5 A
	total battery voltage	24 V
	length of charging cable	10 m
	charging concept	EasyCharge
	charging voltage	230 V
	frequency of power supply	50 Hz
charging time	8 h	
<b>communication</b>		communication via radio, wireless
<b>operation</b>	mode of operation	operation at each column
	activation	all, individual, pair, group
	control	electronic
	Softstart	X
<b>regularisation</b>	synchronisation	proportional valves, infinitely variable
<b>travelling device</b>	travelling device	at each column
	travelling device at front	2 front wheels, hydraulically acting
	travelling device at rear	1 hydraulic pallet jack with twin wheels
	ground clearance at front	80 mm
	ground clearance at rear	100 mm



<b>load securing</b>	load securing	hydraulic and mechanical
<b>dimensions</b>	length	1670 mm
	width	2200 mm
	height	2530 mm
	height of fork (mm)	140 mm
<b>weight</b>	weight per column (kgs)	950 kg
<b>protection class</b>		IP54
<b>surface treatment</b>	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015